



Active System Integration

CP-UNC-T4352L3

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 2 Megapixel CMOS
Minimum Illumination	0.01 Lux@F1.2, 0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto/Manual
AGC Control	Auto/Manual
Back Light Comp	BLC/HLC/DWDR
Lens	6mm (3.6mm,8mm optional)
S/N Ratio	More than 50 dB
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream:1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 1.3 MP Progressive Scan CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 20fps@3M(2048×1536), 25/30fps@1080P
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- 6mm fixed lens (3.6mm,8mm optional)
- IR Range of 30 Mtrs.
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

Smart Phone	iPhone, iPad, Android, Windows Phone
ICR	Auto(ICR) / Color / B/W
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	20 users
IR	IR Range of 30 Mtrs
Operating Temperature	-20°C~+60°C, Less than 95% RH
Power Source	DC12V, PoE(802.3af)
Power Consumption	< 5W
Weatherproof Standard	IP66
Regulatory	CE FCC & RoHs
Dimension	70mm×66mm×160mm
Weight	0.5kg