



Active System Integration

CP-UNC-T5142L3

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 1.3Megapixel CMOS
Minimum Illumination	0.01 Lux@F1.2, 0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC/HLC/DWDR
Lens	2.8mm~12mm
S/N Ratio	More than 50 dB
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream:1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)

Features

- 1/3" 1.3Megapixel PS CMOS Image Sensor
- H.264 and MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280x960)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- 2.8~12mm Varifocal lens
- IR Range of 30 Mtrs, IP66
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

Privacy Masking	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Ch
Audio Output	1 Ch
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	2 Ch
Alarm Out	1 Ch
Interface	1 RS485, 1 RJ45
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	10 users
IR	IR Range of 30 Mtrs
Operating Temperature	-20°C~+60°C(-H : -40°C~+60°C), Less than 95% RH
Power Source	DC12V/AC24V, PoE(802.3af)
Power Consumption	< 7.5W
Weatherproof Standard	IP66
Regulatory	IP66
Dimension	φ104~306.7mm
Weight	1.25Kg