



Active System Integration

## CP-UNC-TP10FL3C-V2

H.264 Video Compression

www.asi.ind.in



### Technical Specification

Image Sensor	1/3" 1.3MP Progressive scan CMOS
Minimum Illumination	0.01 Lux@F1.2, 0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
AGC Control	Auto/Manual
Back Light Comp	BLC/HLC/DWDR
Lens	2.8mm~12mm
S/N Ratio	More than 50 dB
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream:1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)

### Features

- 1/3" 1.3Megapixel PS CMOS Image Sensor
- H.264 and MJPEG dual-stream encoding
- Max 25/30fps@1.3MP
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.8~12mm Varifocal lens
- IR Range of 30 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
Privacy Masking	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Privacy Masking	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI
User Account	20 users
IR	IR Range of 30 Mtrs
Operating Temperature	-30°C~+60°C , Less than 95%RH
Power Source	DC12V, PoE (802.3af)
Power Consumption	< 7W
Weatherproof Standard	IP66
Regulatory	IP66
Dimension	72mm×80mm×212.8mm
Weight	1.25Kg