



Active System Integration

CP-UNC-TP10L3C-V2

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 1.3MP progressive scan CMOS
Minimum Illumination	0. 1Lux/F1.6 (Color) ;0Lux/F1.6(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
AGC Control	Auto/Manual
Back Light Comp	BLC/HLC/DWDR
Lens	3.6mm (6mm,8mm optional)
S/N Ratio	More than 50 dB
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream:1.3M(1~25fps)/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
Privacy Masking	Up to 4 areas

Features

- 1/3" 1.3Megapixel progressive scan CMOS Image Sensor
- H.264 and MJPEG dual-stream encoding
- Max 25/30fps@1.3M/720P
- Max 15fps@1.3M(1280×960)&25/30fps@720P(1280×720)
- DWDR, Day/Night(ICR), 2D-DNR, AWB, AGC, BLC
- 3.6mm fixed lens (6mm,8mm optional)
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Privacy Masking	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	RJ-45 (10/100Base-T)
IR	IR Range of 30 Mtr
Operating Temperature	-30°C~+60°C/ Less than 95%RH (no condensation)
Power Source	DC12V,PoE (802.3af)
Power Consumption	< 6W
Weatherproof Standard	IP66
Dimension	69.4mm x 79.3mm x 173.9mm
Weight	620g