



Active System Integration

## CP-UNC-V5142L2

H.264 Video Compression

www.asi.ind.in



### Technical Specification

Image Sensor	1/3" 1.3Megapixel CMOS
Minimum Illumination	0.05 Lux@F1.4, 0Lux/F1.4(IR on)
Shutter Speed	Auto/Manual 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	2.7mm~9mm
Video Compression	H.264 / MJPEG
S/N Ratio	More than 50dB
Video Streaming	Main Stream : 1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas

### Features

- 1/3" 1.3 MP Progressive Scan CMOS Image Sensor
- H.264 and MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280×960)
- DWDR, Day/Night, 3D-DNR, AWB, AGC, BLC
- 2.7~9mm varifocal lens
- Supports PoE, IP66, IK10
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

## Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Ch
Audio Output	1 Ch
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 Ch
Alarm Out	1 Ch
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	20 Users
IR	IR Range of 20 Mtr.
Operating Temperature	-20°C~+60°C, Less than 90% RH
Power Source	DC12V,PoE(802.3af)
Power Consumption	< 5W
Weatherproof Standard	IK10 & IP66
Regulatory	CE, FCC and RoHS
Dimension	Φ151mm×119mm
Weight	1.25kg