



Active System Integration

CP-UNC-VP10FL2C-V2

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 1.3MP Progressive scan CMOS
Minimum Illumination	0.1Lux/F1.4(Color), 0.01Lux/F1.4(B/W); 0Lux/F1.4(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	2.8 -12mm
Video Compression	H.264 / MJPEG
S/N Ratio	More than 50dB
Video Streaming	Main Stream : 1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
Privacy Masking	Up to 4 areas

Features

- 1/3" 1.3 MP Progressive Scan CMOS Image Sensor
- Max 25/30fps@1.3MP
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night, 3D-DNR, AWB, AGC, BLC
- 2.8 -12mm Varifocal Lens
- IR Range of 20 Mtrs, IP66, IK10, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI
User Account	20 Users
Operating Temperature	-30°C~+60°C , Less than 95%RH
Power Source	DC12V,PoE(802.3af)
Power Consumption	< 6.5W
Weatherproof Standard	IK10 & IP66
Dimension	φ122mm×89mm
Weight	500g