



Active System Integration

CP-UNC-VP13FL2C

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 1.3MP Progressive scan CMOS
Minimum Illumination	0.1lux/F1.4
Shutter Speed	Auto/Manual 1/3~1/10000
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	Off/BLC/HLC/DWDR
Lens	2.8 -12mm
S/N Ratio	More than 50dB
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream: 1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 1.3 MP Progressive Scan CMOS Image Sensor
- Max 25/30fps@ 1.3M(1280×960) and 25/30fps@720P(1280×720)
- H.264 & MJPEG dual-stream encoding
- Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- 2.8 -12mm Varifocal Lens
- Built-in 1/1 alarm in/out
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Ch
Audio Output	1 Ch
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 Ch
Alarm Out	1 Ch
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour. ONVIF Ver. 2.0
User Account	10 Users
IR	IR Range of 20 Mtr.
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V,PoE(802.3af)
Power Consumption	< 6W
Weatherproof Standard	IK10 & IP66
Regulatory	CE, FCC and RoHS
Dimension	Φ151mm×119mm
Weight	1.1kg