



Active System Integration

CP-UNC-B5254S

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 2Megapixel CMOS
Minimum Illumination	0.01Lux/F1.2 (Color), 0.005Lux/F1.2(B/W)
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto/Manual
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
S/N Ratio	More than 50dB
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream: 1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 2MP Exmor CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 50/60fps@1080P
- C/CS Mount Lens
- WDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Ch
Audio Output	1 Ch
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 IN
Alarm Out	1 IN
IVS	Tripwire, Cross Warning Zone, Perimeter Protection, Loitering Detection, Abandoned Object Detection, Missing Object Detection, Illegal Parking, Fast Moving and People counting
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	20 Users
IR	IR Range of 20 Mtr.
Micro SD	Max 32GB
Operating Temperature	-10°C~+60°C, Less than 90% RH
Power Source	AC24V, PoE (802.3af)
Power Consumption	< 12.5W
Dimension	91.8mm×85mm×183.8mm
Weight	1.3 Kg