



Active System Integration

CP-UNC-DP20L2C

H.264 Video Compression

www.asi.ind.in



Features

- 1/3" 2MP PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- 25/30fps@1080P(1920×1080)
- 3.6mm fixed lens (6mm optional)
- DWDR, Day/Night(ICR), 2DNR, AWB, AGC, BLC
- Max. IR distance: 20m
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro

Technical Specification

Image Sensor	1/3" 2MP Progressive scan CMOS
Minimum Illumination	Color: 0.1Lux/F1.2, B/W: 0.01Lux/F1.2; 0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	3.6mm (6mm optional)
S/N Ratio	More than 50dB
Video Compression	H.264 / MJPEG
Video Streaming	1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	10 Users
IR	IR Range of 20 Mtr.
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC24V, PoE
Power Consumption	Max.5W
Weatherproof Standard	IP66
Dimension	φ113mm×86mm
Weight	400g