

2 MP IP Dome Camera



Main Features

- ⇒ 1/3" 2Megapixel progressive scan Exmor CMOS
- ⇒ H.264 & MJPEG dual-stream encoding
- ⇒ 25/30fps@1080P(1920×1080)
- ⇒ DWDR, Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- ⇒ 3.3~12mm varifocal lens
- ⇒ Supports PoE
- ⇒ Built-in 1/1 alarm in/out
- ⇒ Micro SD memory
- ⇒ Mobile Software: CMOB
- ⇒ CMS Software: IPSS

Feature	Specification
Image Sensor	1/3" 2Megapixel Exmor CMOS
Minimum Illumination	Color: 0.1Lux/F1.2, B/W: 0.01Lux/F1.2
Shutter Speed	Auto/Manual 1/3~1/10000
White Balance	Auto
Gain Control(AGC)	Auto/Manual
Lens	3.3~12mm
Back Light Compensation	Off/BLC/HLC/DWDR
Video Compression	H.264/MJPEG
S/N Ratio	more than 50 dB
Video Streaming	Main Stream: 1080P/720P(1 ~ 25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480)/ CIF(352×288)
Privacy Mask	Up to 4 areas
ICR	Auto(ICR) / Color / B/W
Audio Input	1 Channel
Audio Output	1 Channel
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 Channel
Alarm Out	1 Channel
Interface	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP,SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	10 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Micro SD	SD, Max 32GB

Feature	Specification
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V, PoE(802.3af)
Power Consumption	<6W
Regulatory	CE, FCC and RoHS
Dimension	Φ140.3mm x 113.7mm
Weight	0.8kg