



Active System Integration

# CP-UNC-T2212FL3

H.264 Video Compression

www.asi.ind.in



## Technical Specification

Image Sensor	1/2.8" 2MP Progressive scan Sony Exmor CMOS
Minimum Illumination	Color: 0.1Lux/F1.4 ,0Lux (IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
AGC Control	Auto/Manual
Back Light Comp	BLC/HLC/DWDR
Lens	2.8mm~12mm Lens
S/N Ratio	More than 50dB
Video Compression	H.264 / MJPEG
Video Streaming	1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
Privacy Masking	Up to 4 areas

## Features

- 1/2.8" 2MP PS CMOS Image Sensor
- Max 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- 2.8~12mm varifocal lens
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- IR Range of 30 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	20 Users
IR	IR Range of 30 Mtr.
Operating Temperature	-30°C~+60°C , Less than 95%RH
Power Source	DC12V, PoE(802.3af)
Power Consumption	< 4.5W
Weatherproof Standard	IP66
Dimension	72mm × 80mm × 212.8mm
Weight	650g