

CP- UNC-T5254L3

2 MP Full HD IP Bullet Camera

CP PLUS
APEX series



Main Features

- 1/3" 2Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 30 Mtrs.
- 3.3~12mm varifocal lens
- Supports PoE, IP66
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-T5254L3

2 MP Full HD IP Bullet Camera

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Gain Control(AGC)
 Lens
 S/N Ratio
 Video Compression
 Back Light Compensation
 Video Streaming
 Resolution
 Privacy Mask
 ICR
 Audio Input
 Audio Compression
 Audio Output
 Alarm IN
 Alarm Out
 Interface
 Protocol
 Ethernet
 User Account
 IR
 Smart Phone
 Operating Temperature
 Power Source
 Power Consumption
 Weatherproof Standard
 Regulatory
 Dimension
 Weight

Specification

1/3" 2Megapixel CMOS
 0.01 Lux@F1.2, 0Lux/F1.2(IR on)
 Auto/Manual, 1/3~1/10000s
 Auto
 Auto/Manual
 3.3~12mm varifocal lens
 More than 50 dB
 H.264/MJPEG
 BLC / HLC / DWDR
 Main Stream:1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
 1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)
 Up to 4 areas
 Auto(ICR)/Color/B/W
 1 Ch.
 G.711a / G.711u(64kbps) / PCM(128kbps)
 1 Ch.
 2 Ch.
 1 Ch.
 1 RS485, 1 RJ45
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
 RJ-45 (10/100Base-T)
 10 users
 IR Range of 30 Mtr.
 iPhone, iPad, Android, Windows Phone
 -20°C~+60°C(-H: -40°C~+60°C), Less than 95% RH
 DC12V/AC24V, PoE(802.3af)
 <7.5W
 IP66
 CE, FCC and RoHS
 φ104×306.7mm
 1.25kg