



Active System Integration

CP-UNC-T5254L5

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 2Megapixel CMOS
Minimum Illumination	0.05 Lux@F1.4, 0Lux/F1.4(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	3.6mm fixed lens (6mm,8mm optional)
S/N Ratio	More than 50dB
Video Compression	H.264 / MJPEG
Video Streaming	1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 2Megapixel PS CMOS Image Sensor
- Max 25/30fps@1080P(1920×1080)
- H.264 and MJPEG dual-stream encoding
- 3.6mm fixed lens (6mm,8mm optional)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 50 Mtrs.
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Channel
Audio Output	1 Channel
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	2 Channel
Alarm Out	1 Channel
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	20 Users
IR	IR Range of 50 Mtr.
Operating Temperature	-10°C~+60°C, Less than 90% RH
Power Source	DC12V/AC24V, PoE(802.3af)
Power Consumption	< 7.6W
Weatherproof Standard	IP66
Regulatory	CE, FCC and RoHS
Dimension	88mm×76mm×200.2mm
Weight	0.92kg