

# CP- UNC-T5254ZL3

2 MP Full HD IR Bullet Camera - 30Mtr.

CP PLUS  
**APEX** series



## Main Features

- 1/3" 2MP PS CMOS Image Sensor
- Max 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 3 -9mm Varifocal Motorized Lens
- IR Range of 30 Mtrs, Micro SD, IP66, IK10, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-T5254ZL3

## 2 MP Full HD IR Bullet Camera - 30Mtr.

CP PLUS  
**APEX** series

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control(AGC)  
 Video Compression  
 Back Light Compensation  
 S/N Ratio  
 Video Streaming  
 Resolution  
 Privacy Mask  
 ICR  
 Audio Input  
 Audio Output  
 Audio Compression  
 Alarm IN  
 Alarm Out

### Specification

1/3" 2MP Progressive scan CMOS  
 0. 1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W);0Lux/F1.2(IR on)  
 Auto/Manual, 1/3(4)~1/10000s  
 Auto/Manual  
 3 -9mm motorized Lens  
 Auto/Manual  
 H.264/MJPEG  
 BLC/ HLC/ DWDR  
 More than 50dB  
 Main Stream: 1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)  
 1080P(1920×1080)/ 720P(1280×720)/ D1(704×576) / CIF(352×288)  
 Up to 4 areas  
 Auto(ICR)/Color/B/W  
 1 Channel  
 1 Channel  
 G.711a / G.711u/ PCM  
 1 Channel  
 1 Channel  
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI  
 RJ-45 (10/100Base-T)  
 20 Users  
 IR Range of 30 Mtr.  
 iPhone, iPad, Android, Windows Phone  
 Micro SD, Max 64GB  
 -20°C~+60°C (-H: -40°C~+60°C) , Less than 95% RH  
 DC12V (AC 24V optional), PoE (802.3af)  
 Max 7.5W  
 IP66  
 φ104mm×306.7mm  
 1.25Kg.

Protocol

Ethernet

User Account

IR

Smart Phone

Micro SD

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight