



Active System Integration

CP-UNC-T5342L3

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 3MP Progressive scan CMOS
Minimum Illumination	Color: 0. 1Lux/F1.2, 0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	2.8 -12mm Lens
Video Compression	H.264/MJPEG
S/N Ratio	More than 50dB
Video Streaming	Main Stream: 3M(1~20fps)/1080P/720P(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	3M(2048× 1536) / 1080P(1920× 1080) / 720P(1280× 720) / D1(704× 576) / CIF(352× 288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 3MP PS CMOS Image Sensor
- Max 20fps@3M and 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.8 -12mm Varifocal Lens
- IR Range of 30 Mtrs, Micro SD, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI
User Account	20 Users
IR	IR Range of 30 Mtr
Operating Temperature	-20°C~+60°C , Less than 90%RH
Power Source	DC12V (AC 24V optional), PoE (802.3af)
Power Consumption	Max 7.5W
Weatherproof Standard	IP66
Dimension	φ104mm×306.7mm
Weight	1.25Kg