



Active System Integration

## CP-UNC-V5254L2T

H.264 Video Compression

www.asi.ind.in



### Technical Specification

Image Sensor	1/2.8" 2MP Progressive scan CMOS
Minimum Illumination	0.005 Lux@F1.2, 0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	Off/BLC/HLC/DWDR
Lens	2.7mm~12mm
Video Compression	H264/MJPEG
S/N Ratio	More than 50dB
Video Streaming	Main Stream: 1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Resolution	1080P(1920×1080)/ D1(704×576)
Privacy Masking	Up to 4 areas

### Features

- 1/2.8" 2Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 20 Mtrs
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Channel
Audio Output	1 Channel
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	2 Ch
Alarm Out	1 Ch
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	20 Users
IR	IR Range of 20Mtr.
Micro SD	Micro SD, Max 32GB
Operating Temperature	-20°C~+60°C, Less than 90% RH
Power Source	DC12V/AC24V, PoE(802.3af)
Power Consumption	< 7W
Regulatory	CE, FCC and RoHS, IP66, IK10
Dimension	Φ151mm×119mm
Weight	1.25kg