



Active System Integration

CP-UNC-V5254ZL2

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/2.8" 2MP Progressive scan CMOS
Minimum Illumination	0.1lux/F1.4(color), 0Lux/F1.4(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC/HLC/DWDR
Lens	3 -9mm Varifocal Motorized Lens
Video Compression	H264/MJPEG
S/N Ratio	More than 50dB
Video Streaming	Main Stream: 1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1080P(1920×1080)C/ 720P(1280×720)C/ D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 2MP PS CMOS Image Sensor
- Max 20fps@3M and 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 3 -9mm Varifocal Motorized Lens
- IR Range of 20 Mtrs, Micro SD, IP66, IK10, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Channel
Audio Output	1 Channel
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 Ch
Alarm Out	1 Ch
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	20 Users
IR	IR Range of 20Mtr.
Micro SD	Micro SD, Max 64GB
Operating Temperature	-20°C~+60°C, Less than 90% RH
Power Source	DC12V/AC24V, PoE(802.3af)
Power Consumption	Max 5W
Weatherproof Standard	IP66 & IK10
Dimension	Φ151mm×119mm
Weight	1.25kg