



Active System Integration

CP-UNC-B8373

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 3MP Progressive scan CMOS
Minimum Illumination	Color: 0.1Lux/F1.2, B/W: 0.01Lux/F1.2
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
AGC control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	C/CS Mount Lens
S/N Ratio	More than 52 dB
Video Compression	H.264/MJPEG
Video Streaming	Main Stream:3M(1~20fps)/1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	3M(2048× 1536) / 1080P(1920× 1080) / 720P(1280× 720) / D1(704× 576) / CIF(352× 288)
Privacy Masking	Up to 4 areas

Features

- 1/3" 3MP PS CMOS Image Sensor
- Max 25/30fps@3MP
- H.264 and MJPEG dual-stream encoding
- Ultra WDR, Ultra Defog, ROI, EIS, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- C/CS Mount Lens, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR)/Color/B/W
Audio Input	2 channel
Audio Output	1 channel
Audio Compression	G.711a / G.711u
Alarm IN	2 Channel
Alarm Out	1 Channel
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI
User Account	20 Users
Micro SD	Max 64GB
Operating Temperature	-20°C~+60°C , Less than 90% RH
Power Source	DC12V(AC24V optional), PoE (802.3af)
Power Consumption	Max 10W
Dimension	71.4mm×65.5mm×135.4mm
Weight	300g