



Active System Integration

CP-UNC-VP30FL2CD

H.264 Video Compression

www.asi.ind.in



Features

- 1/3" 3Megapixel progressive scan CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 20fps@3.0M(2048×1536)&25/30 fps@1080P(1920×1080)
- 3~12mm varifocal lens
- IR Range max upto 20M
- WDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- Built-in 1/1 alarm in/out
- Supports PoE, IP66, IK10

Technical Specification

Image Sensor	1/3" 3Megapixel CMOS
Minimum Illumination	Color: 0.1Lux@F1.2, B/W: 0.01Lux@F1.2, 0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto
AGC control	Auto/Manual
Back Light Comp	BLC / HLC / WDR (100dB)
Lens	3.3~12mm varifocal lens(2.7~12mm Optional)
S/N Ratio	More than 50 dB
Video Compression	H.264/MJPEG
Video Output	1 channel BNC(1.0Vp-p, 75 Ω)
Video Streaming	Main Stream: 3M(1~15fps)/1080P/720P(1 ~ 25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
Resolution	3.0M(2048×1536) / 1080P(1920×1080) /720P(1280×720) / D1(704×576) /CIF(352×288)/VGA(640×480)
Privacy Masking	Up to 4 areas



Technical Specification

ICR	Auto(ICR)/Color/B/W
Audio Input	1 channel in
Audio Output	1 channel out
Audio Compression	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	1 Input
Alarm Out	1 Output
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S, PSIA
Micro SD	Max 32GB, local storage
User Account	10 Users
Operating Temperature	-25°C~+60°C, 10%~90%
Power Source	DC12V/AC24, PoE(802.3af)
Power Consumption	Max 10W
WeatherProof Standard	IP66 & IK10
Regulatory	CE, FCC, RoHs
Dimension	Φ151mm× 119mm
Weight	1.1Kg