



Active System Integration

CP-UNC-T2322L3

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" 3Megapixel progressive scan CMOS
Minimum Illumination	0. 1Lux/F1.6 (Color) ;0Lux/F1.6(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
AGC control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	3.6mm (6mm,8mm optional)
S/N Ratio	More than 50 dB
Video Compression	H.264/MJPEG

Features

- 1/3" 3Megapixel progressive scan CMOS Image Sensor
- Max 12fps@3M or 25/30fps@1080P/720P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 2D-DNR, AWB, AGC, BLC
- 3.6mm fixed lens (6mm,8mm optional)
- IR Range of 30 Mtrs, IP66
- Max 32GB Hot-swappable SD Card for Local Storage
- Built-in Web server,CMOB & KVMS(CMS)



Active System Integration

www.asi.ind.in

Technical Specification

Video Streaming	Main Stream:3M(1~20fps)/1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	3M(2046×1536)1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)
ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour,, ONVIF Profile S
User Account	20 Users
IR	IR Range of 30 mtr
Operating Temperature	-20°C~+60°C, Less than 95% RH
Power Source	DC12V,PoE (802.3af)
Power Consumption	< 6W
WeatherProof Standard	IP66
Dimension	69.4mm x 79.3mm x 173.9mm
Weight	620g