



Active System Integration

CP-UNC-T4352EL3

H.264 Video Compression

www.asi.ind.in



Features

- 1/3" 3 MP Progressive Scan CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 20fps@3M(2048×1536), 25/30fps@1080P
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- 3.6mm fixed lens (6mm,8mm optional)
- IR Range of 30 Mtrs
- Max 32GB Hot-swappable SD Card for Local Storage
- Built-in Web server,CMOB & KVMS(CMS)

Technical Specification

Image Sensor	1/3" 3 Megapixel CMOS
Minimum Illumination	0.01Lux/F1.2 (Color), 0.005Lux/F1.2(B/W);0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
AGC control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	3.6mm (6mm,8mm optional)
S/N Ratio	More than 50 dB
Video Compression	H.264/MJPEG



Active System Integration

www.asi.ind.in

Technical Specification

Video Streaming	Main Stream:3M(1~20fps)/1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	3.0M(2048 x 1536) /1080P(1920 × 1080) / 720P(1280 × 720) /D1(704 × 576) / CIF(352 × 288)
Privacy Masking	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	20 Users
IR	IR Range of 30 mtrs
Operating Temperature	-20°C~+60°C, Less than 95% RH
Power Source	DC12V,PoE (802.3af)
Power Consumption	< 5W
WeatherProof Standard	IP66
Regulatory	CE, FCC, RoHs & UL
Dimension	168.1mm×66mm×58.4mm