



Active System Integration

CP-UNC-TY10FL5C

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensors	1/3" 1.3Megapixel PS CCD
Minimum Illumination	0.2Lux/F1.6 (Color), 0.01Lux/F1.6(B/W), 0Lux(IR on)
Shutter Speed	Auto/Manual, 1/50~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	8~20mm
Video Compression	H.264, MJPEG
S/N ratio	more than 50dB
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480)/ CIF(352×288)
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Privacy Masking	Up to 4 areas

Features

- 1/3" 1.3MP Progressive scan Sony CCD
- H.264 & MJPEG dual-stream encoding
- Max 12/15fps@1.3M(1280×720)&25/30fps@720P(1280x720)
- D-WDR, Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- 8~20mm varifocal lens
- Built-in 2/1 alarm in/out
- Max. IR LEDs length 50m



Active System Integration

www.asi.ind.in

Technical Specification

ICR	Auto(ICR) / Color / B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	1 Channel
Audio Output	1 Channel
Audio Compressions	G.711a / G.711u(64kbps) / PCM(128kbps)
Alarm IN	2 Channel
Alarm Out	1 Channel
Interface	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP,SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	10 Users
IR	50 mtr.
Micro SD	SD, Max 32GB.
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V(AC24 optional)
Power Consumption	< 15W
Weatherproof Standard	IP66
Dimensions	118.3mm×288.3mm×101mm
Weight	2.5Kg