



Active System Integration

## CP-UNC-CP10L1

H.264 Video Compression

www.asi.ind.in



### Features

- 1/3" 1.3Megapixel CMOS
- H.264 & MJPEG dual-stream encoding
- Max 15fps@1.3M (1280×960)/25/30fps@720P(1280×720)
- DWDR, Day/Night, 2DNR, Auto iris, AWB, AGC, BLC
- 3.6mm fixed lens
- PIR Sensor Range upto 6Mtr.
- CE, FCC & RoHS Certified

### Technical Specification

Image Sensors	1/3" 1.3Megapixel CMOS
Minimum Illumination	0.1lux/F1.8
Shutter Speed	Auto/Manual 1/3~1/10000 (PAL) Auto/Manual 1/4~1/10000(NTSC)
White Balance	BLC / HLC / DWDR
AGC Control	Auto/Manual
Lens	3.6 mm
PIR Sensor	Up to 6m
Video Compression	H.264, MJPEG
S/N ratio	H.264, MJPEG
Video Streaming	Main Stream: 1.3M(1~15fps)/720P/D1(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1.3M(1280x960)/720P(1280x720)/D1/CIF
Privacy Masking	Up to 4 areas



Active System Integration

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Smart Phone	iPhone, iPad, Android, Windows Phone
Interface	RJ-45(10/100Base-T)
Wireless	Yes
Protocol	IPv4/IPv6, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	10 Users
IR	IR Range of 10 mtr.
Operating Temperature	0°C to 40°C (32°F to 104°F)
Power Source	12V DC
Regulatory	CE, FCC & RoHs
Dimensions	66.6×43mm×131.2mm
Weight	0.35kg (0.4kg with bracket)