



Active System Integration

# CP-UNC-CS10L1W

H.264 Video Compression

www.asi.ind.in



## Technical Specification

Image Sensors	1/4" 1 Megapixel CMOS
Minimum Illumination	0.1lux/F1.2
Shutter Speed	Auto/Manual 1/3(4)~1/10000
White Balance	BLC / HLC / DWDR
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	3.6 mm
PIR Sensor	Up to 6m
Video Compression	H.264, MJPEG
S/N ratio	more than 50dB
Video Streaming	Main Stream: 720P(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	720P(1280x720)/D1/CIF
Privacy Masking	Up to 4 areas

## Features

- 1/4" 1 Megapixel CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@720P(1280x720)
- WiFi, DWDR, Day/Night, 3DNR, Auto iris, AWB, AGC, BLC
- 3.6mm fixed lens
- PIR Sensor Range upto 6Mtr.
- IR Range of 10 Mtr.



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

ICR	Auto(ICR) / Color / B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Audio Input	Built-in Mic
Audio Output	Built-in-Speaker
Audio Compressions	G.711a / G.711u / PCM
Alarm IN	1 Channel
Alarm Out	1 Channel
Wireless	Yes
Protocol	IPv4/IPv6, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Ver. 2.0
User Account	10 Users
IR	IR Range of 10 mtr.
Micro SD	Max 64 GB.
Operating Temperature	-30°C~+60°C, Less than 95%RH
Power Source	12V DC
Power Consumption	< 4W
Regulatory	CE, FCC & RoHs
Dimensions	66.6mm × 99.5mm × 131.2mm
Weight	0.35kg (0.4kg with bracket)