



Active System Integration

CP-UNC-D1011

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensors	1/4" 1Megapixel Progressive Scan CMOS
Minimum Illumination	Color: 0.1Lux/F1.2, B/W: 0.05Lux
Shutter Speed	Auto/Manual: 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	3.6mm (2.8mm, 6mm, 8mm optional)
Video Compression	H.264, MJPEG
S/N ratio	more than 50dB
Video Streaming	720P@25 fps

Features

- 1/4" 1 MP Progressive Scan CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- 25/30fps@720P
- DWDR, AWB, AGC, BLC, 3D-DNR
- 3.6mm fixed lens (2.8 mm, 6mm, 8mm optional)
- Supports PoE
- Mobile Software: iCMOB, gCMOB



Active System Integration

www.asi.ind.in

Technical Specification

Resolution	720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas
ICR	Auto(ICR) / Color / B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	10 Users
Operating Temperature	-10°C~+60°C, 10%~90%
Power Source	DC12V, PoE(802.3af)
Power Consumption	Max 3W
Dimensions	Φ110mm x 54mm
Weight	200g