



Active System Integration

## CP-UNC-T1011L2

H.264 Video Compression

www.asi.ind.in



### Technical Specification

Image Sensors	1/4" 1Megapixel Progressive Scan CMOS
Minimum Illumination	Color: 0.1Lux/F1.2, 0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual: 1/3~1/10000s
White Balance	Auto
AGC Control	Auto/Manual
Back Light Comp	BLC / HLC / DWDR
Lens	3.6mm (2.8mm, 6mm optional)
Video Compression	H.264, MJPEG
S/N ratio	more than 50dB
Video Streaming	720P@25 fps

### Features

- 1/4" 1 MP Progressive Scan CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- 25/30fps@720P
- DWDR, Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 3.6mm fixed lens (6mm optional)
- IR Range of 20 Mtr
- Supports PoE, IP66



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Resolution	720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas
ICR	Auto(ICR) / Color / B/W
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	10 Users
IR	IR Range of 20 mtr.
Operating Temperature	-30°C~+60°C, Less than 95% RH
Power Source	DC12V, PoE(802.3af)
Power Consumption	Max 4W
Weatherproof Standard	IP66
Dimensions	Φ70mm × 66mm × 160mm
Weight	0.5Kg