



Active System Integration

CP-UNK-331

Preset Position, Auto Scan, Auto Pan

www.asi.ind.in



Technical Specification

Keyboard KeyPanel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
Keyboard Connector	RJ-45,RS232,RS485,RS422,USB
Keyboard Communication	Direct mode, Network mode

Features

- 3 Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Full HD 1080p live view; Support HDMI & VGA sync output
- Auxiliary Functions
- Network Video Server
- On-Screen Menu & User Operation Procedure Tips
- Connect KVMS Pro via USB



Active System Integration

www.asi.ind.in

Technical Specification

Power Consumption	5W
Direct Mode	Interface: RS232/RS485
Resolution	LCD, 75.2mm x 33.85mm
Display	1/4/8/9/16
Power Supply	Power adapter, input 100V~240V 50Hz / 60Hz,output DC12V/1000mA
Working Temp	-10~+55°C
Working Humidity	10%~90%
Atmosphere Pressure	86kpa~106kpa
Dimensions	330mmx160(140)mmx37.5(21)mm (W× D×H) (height: 100mm including
Weight	2.5KG