



Active System Integration

## CP-UNC-E2234

H.264 Video Compression

www.asi.ind.in



### Features

- 1/3" 2 Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P & 25/30fps@SXGA & 25/30fps@720P
- Day/Night(ICR), 2D-DNR, AWB, AGC, BLC
- 1.25mm Fish-Eye lens
- Supports PoE
- Mobile Software: iCMOB, gCMOB

### Technical Specification

Image Sensor	1/3" 2 Megapixel CMOS
Minimum Illumination	0.1 Lux@F1.4
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto
AGC control	Auto / Manual
Back Light Compensation	BLC
Lens	1.25mm
Video Compression	H.264/MJPEG
Video Streaming	Main Stream: 1080P/SXGA(1~25fps)/720P(1 ~ 25fps), Extra Stream: D1/CIF(1 ~ 25fps)



Active System Integration

www.asi.ind.in

## Technical Specification

Resolution	1080P(1920×1080) / SXGA(1280×1024)720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Masking	Up to 4 areas
Smart Phone	iPhone, iPad, Android, Windows Phone
ICR	Auto(ICR)/Color/B/W
Interface	1 RS485, 1 RJ45
Protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
User Account	10 Users
Operating Temperature	-20°C~+60°C(-H : -40°C~+60°C), Less than 95% RH
Power Source	DC12V, PoE(802.3af)
Power Consumption	< 2.5W
Regulatory	CE, FCC & RoHs
Dimensions	Φ110×54mm
Weight	250g