



Active System Integration

# CP-UNP-2013SL10

H.264 Video Compression

www.asi.ind.in



## Technical Specification

Image Sensor	1/3" Exmor CMOS
Effective Pixels	1280(H) x 960(V)
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
S/N Ratio	More than 50dB
Minimum illumination	Color: 0.05Lux@F1.6, B/W: 0.005Lux@F1.6
Focal Length	4.7mm ~ 94mm
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Angle of View	H: 54.1° ~ 3.2°
Focus Control	Auto/Manual
Electronic Shutter	1/1 ~ 1/30,000s
AGC control	Auto / Manual
Back Light Compensation	BLC / HLC /DWDR
Privacy Masking	Up to 24 areas
Optical Zoom	20x
Digital Zoom	16x
Smart Phone	iPhone, iPad, Android, Windows Phone

## Features

- 1/3" Exmor CMOS Image sensor
- Powerful 20x Optical and 16x Digital zoom
- DWDR, Day/Night(ICR), Ultra DNR
- Up to 255 Presets, 8 Tour, 5 Pattern, 5 Auto scan
- Max 240°/s pan speed, 360° endless pan rotation
- IR Range of 100 Mtr.
- Built-in 2/1 alarm in/out, IP66



## Technical Specification

Special Features	IR Range upto 100m, Up to 255 Presets, 8 Tour, 5 Pattern, 5 Auto scan
Power up action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Pan/ Scan/ Tour/ Pattern if there is no command in the specified period
Time task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Day/Night: IR Cut Filter	Auto(ICR) / Color / B/W
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream: 1.3M/720P(1 ~ 25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
Audio Compression	G.711a / G.711u(32kbps)/ PCM(128kbps)
Audio Streaming	1/1 channel In/Out
Protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
Alarm	2/1 channel In/Out
User Account	20 Users
Memory	Micro SD, Max 64GB
Operating Temperature	-40°C ~ 60°C / Less than 90% RH
Weatherproof Standard	IP66
Dimensions	Φ204.7(mm) x 359.9(mm)
Weight	7.8 kg
Power Source	AC 24V/2.2A(±10%)
Power Consumption	10.5W, 26W (IR on, Heater on)