



Active System Integration

CP-UNP-2030L10D

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" CMOS
Effective Pixels	2048(H) x 1536(V), 3 Megapixels
Synchronization	Internal
Video Output	BNC(1.0Vp-p/75Ω)
S/N Ratio	More than 50dB
Minimum illumination	Color: 0.05Lux@F1.6, B/W: 0.005Lux@F1.6
Focal Length	4.7mm ~ 94mm
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Angle of View	H: 58.2° ~ 2.9°
Focus Control	Auto/Manual
Electronic Shutter	1/1 ~ 1/30,000s
AGC control	Auto / Manual
Back Light Compensation	BLC / HLC / WDR (100db, 1080P mode)
Privacy Masking	Up to 24 areas
Optical Zoom	20x
Digital Zoom	16x

Features

- 1/3" CMOS
- Powerful 20x optical zoom and 16x digital zoom
- H.264 & MJPEG dual-stream encoding and JPEG image capture
- WDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, AWB, AGC,BLC
- Max 240°/s pan speed, 360° endless pan rotation
- Max 15fps@3Mp, 25/30fps@1080p resolution
- The longest distance of IR LED is over 100m
- Up to 255 preset, 5 auto scan, 8 tour, 5 pattern



Active System Integration

www.asi.ind.in

Technical Specification

Manual Speed	Pan: 0.1° ~300° /s; Tilt: 0.1° ~250° /s
Presets	255
Preset Speed	Horizontal: 400°/s, Vertical: 300°/s
Time task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Day/Night: IR Cut Filter	Auto(ICR) / Color / B/W
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream: 1.3M/720P(1 ~ 25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
Audio Compression	G.711a / G.711u(32kbps)/ PCM(128kbps)
Audio Streaming	1/1 channel In/Out
Networking	RJ-45 (10/100Base-T), 1 RS485
Alarm	7/2 alarm input/output
User Account	20 Users simultaneously
Memory	Micro SD, Max 32GB
Operating Temperature	-40°C ~ 60°C / Less than 90% RH
Weatherproof Standard	IP67
Dimensions	Φ229.6(mm) x 381.5(mm)
Weight	7kg
Power Source	AC 24V/3A (±10%)/ DC12V optional
Power Consumption	17W, 35W(IR on, Heater on)
Regulatory	CE, FCC, RoHS & UL