



Active System Integration

CP-UNP-2030L15D

H.264 Video Compression

www.asi.ind.in



Technical Specification

| | |
|-------------------------|---|
| Image Sensor | 1/3" CMOS |
| Effective Pixels | 2048(H) x 1536(V), 3 Megapixels |
| Video Output | BNC(1.0Vp-p/75Ω), PAL / NTSC |
| S/N Ratio | More than 50dB |
| Minimum illumination | Color: 0.05Lux@F1.6, B/W: 0.005Lux@F1.6 |
| White Balance | Auto, ATW, Indoor, Outdoor, Manual |
| Angle of View | H: 55.4° ~ 2.9° |
| Focus Control | Auto/Manual |
| Electronic Shutter | 1/1 ~ 1/30,000s |
| AGC control | Auto / Manual |
| Back Light Compensation | BLC / HLC / WDR(120dB) |
| Privacy Masking | Up to 24 areas |
| Optical Zoom | 20x |
| Digital Zoom | 16x |
| Smart Phone | iPhone, iPad, Android, Windows Phone |
| Pan Travel | 0° ~ 360° endless, Pan Speed: 0.1° ~ 200°/sec |

Features

- 1/3" CMOS Image sensor
- Max.15fps@3MP, 25fps@1080p resolution
- Powerful 20x Optical and 16x Digital zoom
- WDR, Day/Night(ICR), DNR (2D&3D)
- Up to 255 Presets, 8 Tour, 5 Pattern, 5 Auto scan
- Max 240°/s pan speed, 360° endless pan rotation
- IR Range of 150 Mtr.



Active System Integration

www.asi.ind.in

Technical Specification

| | |
|--------------------------|---|
| Presets | 255 |
| Preset Speed | Pan: 240° /s; Tilt: 200° /s |
| Special Features | WDR, Day/Night(ICR), DNR (2D&3D), Auto iris, Auto focus, 5 Auto Pattern, 8 Auto Tour, 5 auto scan |
| Power up action | Auto restore to previous PTZ and lens status after power failure |
| Idle Motion | Activate Preset/ Pan/ Scan/ Tour/ Pattern if there is no command in the specified period |
| Time task | Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time |
| Day/Night: IR Cut Filter | Auto(ICR) / Color / B/W |
| Video Compression | H.264 / MJPEG |
| Video Streaming | Main Stream: 3M(1~15fps)/1080P/720P(1 ~ 25/30fps), Sub Stream: 25/30fps@D1/CIF |
| Audio Compression | G.711a / G.711u(32kbps)/ PCM(128kbps) |
| Audio Streaming | 1/1 channel In/Out |
| Alarm | 7/2 channel In/Out |
| User Account | 20 Users |
| Dimensions | Φ252(mm) x 384.3 (mm) |
| Weight | 6.75 kg |
| Power Source | AC 24V/3A(±16%) |
| Power Consumption | 20W, 43W (IR on, Heater on) |