



Active System Integration

CP-UNP-1813L10DH

H.264 Video Compression

www.asi.ind.in



Technical Specification

Image Sensor	1/3" CCD
Effective Pixels	1280(H) x 960(V)
Synchronization	Internal
Video Output	BNC(1.0Vp-p/75Ω), PAL / NTSC
S/N Ratio	More than 50dB
Minimum illumination	0.05Lux/F1.6
Focal Length	4.7mm~84.6mm
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Angle of View	H: 55.2°~3.2°
Focus Control	Auto/Manual
Electronic Shutter	PAL:1/3~1/10000s NTSC:1/4~1/10000s
AGC control	Auto / Manual
Back Light Compensation	BLC / HLC / WDR
Privacy Masking	Up to 24 areas
Remote Operations	Monitor, PTZ control, Voice Intercom, System setting, Playback
Optical Zoom	18x
Digital Zoom	12x
Smart Phone	iPhone, iPad, Android, Windows Phone

Features

- 1/3" CCD
- H.264 & MJPEG dual-stream encoding
- Powerful 18x optical zoom and 12x digital zoom
- Max.25/30fps@1.3M(1280×960) & 720P resolution
- WDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, AWB, AGC,BLC
- Max 240°/s pan speed, 360° endless pan rotation
- The longest distance of the build-in IR LED is over 100m
- Up to 255 presets, 5 auto scan, 8 tour, 5 pattern



Active System Integration

www.asi.ind.in

Technical Specification

Presets	255
Preset Speed	Pan: 400°/s; Tilt: 300°/s
Power up action	Auto restore to previous PTZ and lens status after power failure
Time task	Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time
Day/Night: IR Cut Filter	Auto(ICR) / Color / B/W
Video Compression	H.264 / MJPEG
Video Streaming	Main Stream: PAL: 1.3M(1~12fps), 720P(1~25fps), Extra Stream: PAL: D1/CIF/QCIF (1~25fps)
Audio Compression	G.711a / G.711u(32kbps)/ PCM(128kbps)
Audio Streaming	1/1 channel In/Out
Networking	RJ-45 (10/100Base-T), 1 RS485
Alarm	7/2 channel In/Out
Supported Web Browser	Windows – Microsoft Internet Explorer 6.x or later
User Account	20 Users simultaneously
Operating Temperature	-40°C ~ 60°C
Dimensions	Φ222(mm) x 322 (mm)
Weight	5.0kg
Power Source	AC 24V/3A(±10%)
Power Consumption	15W, 40W(Heater on)
Regulatory	CE, FCC, RoHS