



Active System Integration

# CP-UNS-6168R

Dual-Core 64-bit Processor

www.asi.ind.in



## Technical Specification

Processor	Intel Sandy Bridge quad-core processor
Operating System	Embedded Linux
Mother Board	Server Class(24/7 operation)
Memory	4G
User Interface	WEB GUI
Input	192ch@D1,96ch@720P,48ch@1080P
Recording	D1: 120 channels, CIF: 400 channels
Hard Disk	16 SATA II ports,16 HDDs supported(each one up to 3TB)

## Features

- IPSAN / NAS integration solutions
- Support single disk, support various data protection modes such as RAID0, RAID1, RAID5
- Fault-tolerant data protection mechanisms for the video surveillance system
- High-performance, scalability, easy for data storage and file sharing
- Support common industry network protocol such as SAMBA, NFS, ISCSI, CIFS, FTP, HTTP etc



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

HDD Expansions	Support up to four expansion device
Ethernet	4 RJ-45 10/100/1000Mbps
Expansion Interface	2 Mini SAS
HDD Hot Standby	Support global HDD Hot Standby
Power Supply	100V-240Vac, 47-63Hz
Power Consumption	< 400W(include HDD), < 200W(exclude HDD)
Working Temp	0°C~40°C
Working Humidity	10%~80%(Non-Condensation)
Weight	23Kg
Dimensions	448mm x 490.4mm x 133.2mm