



Active System Integration

CP-UNR-404T2-P4

Dual-Core embedded Processor

www.asi.ind.in



Technical Specification

Processor	Dual-core embedded processor
Operating System	Embedded Linux
IP Camera Input	4 channel
Two-way-talk	1 channel Input, 1 channel Output, RCA
User Interface	GUI
Video Output	1 HDMI, 1 VGA
Compression	H.264 / MJPEG
Video Resolution	2560×1920, 2048×1536, 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Video Recording	Max 128 Mbps
Video Display Split	1/4
Motion Detection	MD Zones: 396(22×18)
Video Loss	Supports
Camera Blank	Supports
Alarm Input	4 Channel
Alarm Output	2 Channel
Hard Disk	2 SATA ports, up to 8TB, Raid (Redundancy)
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop

Features

- 4 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras



Active System Integration

www.asi.ind.in

Technical Specification

Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Internal SATA burner/ Network
Interface Ports	1 HDMI, 1 VGA, 2 USB2.0, 1 RS485, 1 RS232, 1 RJ45
Max User Account	128 users
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3
Ethernet	1 RJ-45 port (10/100M/1000M)
Power Supply	DC12V/4A, PoE: DC48V/1.04A
Power Consumption	NVR: 20W (without HDD), PoE: Max 25.5W for single port
Working Temp	-10 ~ +55°C / 10~90%RH / 86~106kpa
Dimensions	375mm×285mm×50mm
Weight	2 Kg (without HDD)