



Active System Integration

CP-UNR-408T2

Dual-Core embedded Processor

www.asi.ind.in



Technical Specification

Processor	Dual-core embedded processor
Operating System	Embedded Linux
IP Camera Input	8 channel
Two-way-talk	1 channel Input, 1 channel Output, RCA
User Interface	GUI
Video Output	1 HDMI, 1 VGA
Compression	H.264 / MJPEG 2560 × 1920, 2048 × 1536, 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Video Resolution	2560×1920, 2048×1536, 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Video Recording	Max 128 Mbps
Video Display Split	1/4/8/9
Motion Detection	MD Zones: 396(22×18)
Video Loss	Supports
Camera Blank	Supports
Alarm Input	4 Channel
Alarm Output	2 Channel
Hard Disk	2 SATA ports, up to 8TB, Raid (Redundancy)
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen

Features

- 8 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview&playback
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- HDMI / VGA simultaneous video output



Active System Integration

www.asi.ind.in

Technical Specification

Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Internal SATA burner/ Network
Interface Ports	1 HDMI, 1 VGA, 2 USB2.0, 1 RS485, 1 RS232, 1 RJ45
Max User Account	128 users
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3
Ethernet	1 RJ-45 port (10/100M/1000M)
Power Supply	DC12V/4A
Power Consumption	20W(without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimensions	375mm×285mm×50mm
Weight	2 Kg (without HDD)