



Active System Integration

CP-UNR-108M1

Dual-Core embedded Processor

www.asi.ind.in



Technical Specification

Processor	Dual-core embedded processor
Operating System	Embedded Linux
IP Camera Input	8 channel
User Interface	GUI
Video Output	1 HDMI, 1 VGA
Compression	H.264 / MJPEG
Video Resolution	1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Video Recording	Max 48 Mbps
Video Display Split	1/4/8/9
Motion Detection	MD Zones: 396(22×18)
Video Loss	Supports
Camera Blank	Supports
Hard Disk	1 SATA port, up to 4TB
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop

Features

- 8 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 48Mbps incoming bandwidth
- Support 1 SATA HDDs up to 4TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.0 conformance



Active System Integration

www.asi.ind.in

Technical Specification

Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
Interface Ports	1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45
Max User Account	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP
Ethernet	RJ-45 port (10/100M/1000M)
Power Supply	DC12V/2A
Power Consumption	12W (without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimensions	205mm×205mm×45mm
Weight	500g (without HDD)