



Active System Integration

CP-UNR-408T1

Dual-Core embedded Processor

www.asi.ind.in



Technical Specification

| | |
|---------------------|--|
| Processor | Dual-core embedded processor |
| Operating System | Embedded Linux |
| IP Camera Input | 8 channel |
| Two-way-talk | 1 channel Input, 1 channel Output, RCA |
| User Interface | GUI |
| Video Output | 1 HDMI, 1 VGA |
| Compression | H.264 / MJPEG |
| Video Resolution | 2560×1920, 2048×1536, 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768 |
| Video Recording | Max 80 Mbps |
| Video Display Split | 1/4/8/9 |
| Motion Detection | MD Zones: 396(22×18) |
| Video Loss | Supports |
| Camera Blank | Supports |
| Hard Disk | 1 SATA ports, up to 4TB |
| Trigger Events | Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen |
| Recording Mode | Manual, Schedule(Regular(Continuous), MD, Alarm), Stop |

Features

- 8 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview & playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 4TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras



Active System Integration

www.asi.ind.in

Technical Specification

| | |
|-------------------|---|
| Search Mode | Time/Date, Alarm, MD & Exact search (accurate to second), Smart search |
| Playback | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom |
| Backup Mode | USB Device / Internal SATA burner/ Network |
| Interface Ports | 1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45 |
| Max User Account | 128 users |
| Record Interval | 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec |
| Smart Phone | iPhone, iPad, Android, Windows Phone |
| Protocols | HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3 |
| Ethernet | 1 RJ-45 port (10/100M/1000M) |
| Power Supply | DC12V/2A |
| Power Consumption | 10W (without HDD) |
| Working Temp | -10 ~ +55°C / 10~90%RH / 86~106kpa |
| Dimensions | 325mm × 240mm × 45mm |
| Weight | 1.25 Kg (without HDD) |