



Active System Integration

# CP-UNR-332T2

Dual-Core embedded Processor

www.asi.ind.in



## Technical Specification

Processor	Dual-core embedded processor
Operating System	Embedded Linux
IP Camera Input	32 channel
Two-way-talk	1 channel Input, 1 channel Output, RCA
User Interface	GUI
Compression	H.264 / MJPEG
Video Resolution	5MP(2560×1920) / 3MP(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Video Recording	Max 128 Mbps
Video Display Split	1/4/8/16
Motion Detection	MD Zones: 396(22×18)
Video Loss	Supports
Camera Blank	Supports

## Features

- 32 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 160Mbps incoming bandwidth
- Up to 5Mp resolution
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.0 conformance



Active System Integration

www.asi.ind.in

## Technical Specification

Alarm Input	8 Channel
Alarm Output	3 Channel
Hard Disk	2 SATA ports
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Backup Mode	USB Device / eSATA Device / Network
Interface Ports	1 HDMI, 1 VGA, 3 USB2.0, 1 RJ45, 1 RS232, 1 RS485
Max User Account	20 users
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Smart Phone	iPhone, iPad, Android, Windows Phone
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.0
Ethernet	RJ-45 port (10/100M/1000M)
Power Supply	DC12V
Power Consumption	20W (without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimensions	375mm × 285mm × 50mm
Weight	2.3KG(without HDD)