



Active System Integration

## CP-VXC-L2024P-R

Advance Algorithm for Reliable Operation

[www.asi.ind.in](http://www.asi.ind.in)



### Technical Specification

Fingerprint Capacity	1000
Log Capacity	50000
Sensor	Optical Sensor
Scan Area	22mm*18mm
FRR	0.001%
FAR	0.00001%
LCD	Blue LCD
Identification Mode	FP, ID+FP, ID+PW

### Features

- New generation fully sealed, waterproof and dustproof fingerprint sensor.
- RS485, USB and TCP/IP network interface
- Advanced Algorithm for Reliable operation
- Stylish blue LCD. Musical buzzer
- 1000 Fingerprint Capacity
- Multiple identification method: fingerprint only, ID + password, ID + fingerprint



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

Identification Time	< 1 second
Resolution	500 DPI
Fingerprint Image Display	Yes
Communication	RS485, TCP/IP & USB
Self-defined Status	16
Work Code	Yes
Working Current	Yes
Operating Temperature	-10°C-60°C
Humidity	20%-80%
ESD Tolerance	>15000V
Certifications	FCC, CE, RoHS
Operating Voltage	DC12V
Dimensions	74(w)*144(h)*40(d)mm