



Active System Integration

NVS0104DH-4K

Standalone viewers

www.asi.ind.in



Features

- Designed for standalone operator viewers
- H.265/H.264/MPEG-4 video decoding
- 1ch@12Mp / 4ch@4K / 16ch@1080P / 64ch@D1 decoding ability
- Support multiple resolution decoding: up to 8Mp and 12Mp network video
- 1ch HDMI/VGA output, HDMI support Ultra HD 4K output
- Support 1 / 4 / 9 / 16 / 25 / 36 / 64 display split
- Support audio, alarm, bi-directional talk, RS485
- Local GUI support mouse operation directly

Technical Specification

Model	NVS0104DH-4K
System	
Processor	Intel x86 processor
Operating System	Linux
Performance	
Video Format	MPEG4/H.264/MJPEG/H.265
Audio Format	PCM/G.711
Decoding Resolution	QCIF/CIF/2CIF/HD1/D1/960H/720P/1080P/3Mp/5Mp/8Mp/12Mp
Video Output	1ch HDMI, 1chVGA
Display Resolution	3840*2160/1920*1080/1280*1024/1280*720/1024*768
Audio Output	HDMI
Communication Interface	1 RJ45 network port (10M/100M/1000M); 1 RS232; RS485
Bi-directional Talk	1 channel, RCA in / RCA out (2Vrms, 10K ohms)
Alarm Input	4ch
Alarm Output	4ch relay out (30VDC 1A, 125VAC, 0.5A)



Active System Integration

www.asi.ind.in

Technical Specification

Others	
Power Supply	DC12V, 3.3A
Power Consumption	≤20W
Working Temperature	-10°C~+55°C
Working Humidity	10% ~ 95%, 86Kpa ~ 106Kpa
Unit Dimension	440×300×42.1
Weight	3.5Kg