



Active System Integration

PFM800

Coaxial Video Connector

www.asi.ind.in



Features

- Transmission Signal
- Transmission Distance
- Coaxial Video Connector
- Twisted-pair Video Connector
- Compatible Format
- Anti-interference
- BNC Male
- UTP Cable

Technical Specification

Model	DH-PFM800
Properties	
Transmission Signal	1 channel
Transmission Distance	720P: 400M (max) 1080P: 250M (max)
Category Type	UTP CAT5/5E/6 (R < 10Ω/100M)
Video Transmission Properties And Port	
Coaxial Video Connector	BNC-M
Twisted-pair Video Connector	Push-terminal
Compatible Format	HDCVI
Resolution	720P/1080P
Anti-interference	>60db



Active System Integration

www.asi.ind.in

Technical Specification

Protection	
ESD	1a contact discharge electricity level 3
	1b air discharge electricity level 3
	Per:IEC61000-4-2
Coaxial Cable Connector	2KV(common-code) Per:IEC1000-4-5
UTP Cable Connector	2KV(different-code),4KV(common-code),Per:IEC1000-4-5
Impedance	
BNC Male	75 ohms
UTP Cable	100 ohms
Physical Properties	
Dimension(L*W*H)	53mm*20mm*17mm
Shell	ABS
Color	Black
N.W.	25G
Stability	
MTBF	>10000H
Environmental	
Operating Temperature	-10~55°C
Storage Temperature	-20~70°C
Humidity	0~95%(non-condensing)