



Active System Integration

# iHCVR5104-5108HE-F

4/8 channel 720P Mini 1U Face Detection iHCVR

www.asi.ind.in



## Technical Specification

Model		DH- iHCVR5104HE-F	DH- iHCVR5108HE-F
<b>System</b>			
Main Processor		Embedded processor	
Operating System		Embedded LINUX	
<b>Video</b>			
Input		4 channel, BNC	8 channel, BNC
Standard	HDCVI	1080P/720P HDCVI Camera	
	IP	1080P/720P/D1/CIF IP Camera	
<b>Audio</b>			
Input		1 channel, RCA	
Output		1 channel, RCA	
Two-way Talk		Reuse audio input/output channel 1	

## Features

- Support 1ch face detection, instant playback and face index playback
- Up to 4/8 cameras with 1080p realtime preview
- H.264 dual-stream video compression
- iHCVR5104/5108HE-F: All channel 720P realtime recording
- HDMI/VGA simultaneous video output
- 4/8 channel synchronous realtime playback, GRID interface & smart search
- 3D intelligent positioning with Dahua PTZ dome camera
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS



### Technical Specification

#### Display

Interface	1 HDMI, 1 VGA	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768, 800×600	
Display Split	1/4	1/4/8/9
Privacy Masking	4 rectangular zones (each camera)	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	

#### Recording

Video/Audio Compression	H.264/G.711	
Resolution	1080P(1920×1080)/720P(1280×720)/960H(960×576/960×480)/D1/4CIF(704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120)	
Record Rate	Main Stream:	1080P/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps)
	Extra Stream	CIF/QCIF(1~25/30fps), D1(1~12/15fps)
Bit Rate	48~6144Kb/s	
Record Mode	Manual, Schedule(Regular(Continuous), MD), Stop	
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	

#### Video Detection & Alarm

Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips	
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank	
Alarm Input	4 channel	16 channel
Relay Output	3 channel	



## Technical Specification

<b>Playback &amp; Backup</b>	
Sync Playback	1/4 1/4/9 1/4/9/16
Search Mode	Time/Date, MD & Exact search (accurate to second)
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Internal SATA burner/Network
<b>Network</b>	
Ethernet	RJ-45 port (10/100M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android, Windows Phone
<b>Storage</b>	
Internal HDD	1 SATA port, up to 4TB
<b>Auxiliary Interface</b>	
USB Interface	2 ports(1 Rear), USB2.0
RS485	1 port, For PTZ Control
<b>General</b>	
Power Supply	DC12V/2A
Power Consumption	10W(without HDD)
Working Environment	-10°C ~+55°C / 10%~90%RH / 86~106kpa
Dimension(W×D×H)	Mini 1U, 325mm×255mm×55mm
Weight	1.5KG(without HDD)