



Active System Integration

DH-HAC-HDBW2220R-Z

2.4MP 1080P Vandal proof IR HDCVI Dome camera

www.asi.ind.in



Features

- 1/3" 2.4Megapixel CMOS
- High resolution of 720TVL
- Day/Night(ICR), AWB, AGC, BLC
- 2.7~12mm vari-focal lens
- Max. IR LEDs length 30m, Smart IR
- IP66, IK10, DC12V

Technical Specification

Model	DH-HAC-HDBW2220RP-Z	DH-HAC-HDBW2220RN-Z
	Camera	
Image Sensor	1/2.8" 2.4Megapixel CMOS	
Effective Pixels	1984(H)×1225(V)	
Electronic Shutter	1/3s~1/100,000s	
Video Frame Rate	25/50fps@720P	30/60fps@720P
Synchronization	Internal	
Mini. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on	
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)	



Active System Integration

www.asi.ind.in

Technical Specification

Camera Features	
Max. IR LEDs Length	20m, Smart IR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D
Lens	
Focal Length	2.7~12mm
Lens Type	Manual / Fixed Iris
Mount Type	Φ14
General	
Power Supply	DC12V±10%
Power Consumption	4.8W
Working Environment	-40°C~+60°C / Less than 95%RH (no condensation)
Ingress Protection	IP66 & IK10
Dimensions	Φ122mm×89mm
Weight	0.45kg