



Active System Integration

DH-HAC-HFW2120D-B

1.4 MP 720P Water proof IR HDCVI camera

www.asi.ind.in



Technical Specification

Model	DH-HAC-HFW2100DP-B	DH-HAC-HFW2100DN-B
	Camera	
Image Sensor	1/3" 1.4Megapixel CMOS	
Effective Pixels	1305(H)×1049(V)	
Electronic Shutter	1/3s~1/100,000s	
Video Frame Rate	25/30/50/60fps @720P	25/30/50/60fps @720P
Synchronization	Internal	
Mini. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on	
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)	

Features

- 1/3" 1.4Megapixel CMOS
- 25/30fps@1080P,25/30/50/60fps@720P
- Day/Night(ICR), AWB, AGC, BLC
- 2.7~12mm vari-focal lens
- Max. IR LEDs length 30m, Smart IR
- IP66, DC12V



Active System Integration

www.asi.ind.in

Technical Specification

Camera Features	
Max. IR LEDs Length	20m, Smart IR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	2D
Lens	
Focal Length	2.7~12mm
Lens Type	Manual / Fixed Iris
Mount Type	Φ14
General	
Power Supply	DC12V±10%
Power Consumption	4.8W
Working Environment	-40°C~+60°C / Less than 95%RH (no condensation)
Ingress Protection	IP66 & IK10
Dimensions	200.2mm×89.1mm×161.2mm
Weight	0.58kg