



Active System Integration

## DH-IPC-HD1200C-W

1 MP HD Wi-Fi IR Mini Dome camera

www.asi.ind.in



### Features

- 1/4" 1Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- Day/Night(ICR), AWB, AGC, BLC
- 3.6mm fixed lens (2.8mm,6mm optional)
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- DC12V

### Technical Specification

| Model                    | DH-IPC-HD1200C-W                      |
|--------------------------|---------------------------------------|
|                          | <b>Camera</b>                         |
| Image Sensor             | 1/4" 1Megapixel progressive scan CMOS |
| Effective Pixels         | 1280(H)x720(V)                        |
| Scanning System          | Progressive                           |
| Electronic Shutter Speed | Auto/Manual 1/3 (4) ~1/10000          |
| Min. Illumination        | 0.1Lux/F1.8(color), 0Lux/F1.8(IR on)  |
| S/N Ratio                | More than 50dB                        |
| Video Output             | N/A                                   |
|                          | <b>Camera Features</b>                |
| Max. IR LEDs Length      | N/A                                   |
| Day/Night                | Auto(Electronic) / Color / B/W        |
| Backlight Compensation   | BLC /HLC /DWDR                        |
| White Balance            | Auto                                  |
| Gain Control             | Auto/Manual                           |
| Noise Reduction          | 3D                                    |
| Privacy Masking          | Up to 4 areas                         |



**Active System Integration**

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

### Auxiliary Interface

|                  |     |
|------------------|-----|
| Memory Slot      | N/A |
| RS485            | N/A |
| Alarm            | N/A |
| PIR Sensor Range | N/A |

### General

|                     |                              |
|---------------------|------------------------------|
| Power Supply        | DC12V                        |
| Power Consumption   | <4W                          |
| Working Environment | -30°C~+50°C, Less than 95%RH |
| Ingress Protection  | N/A                          |
| Vandal Resistance   | N/A                          |
| Dimensions          | Φ110×54mm                    |
| Weight              | 0.25kg                       |