



Active System Integration

## DH-IPC-HDBW1000E-W

1MP HD Wi-Fi IR Mini Dome Camera

www.asi.ind.in



### Features

- 1/4" 1Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- Day/Night(ICR), AWB, AGC, BLC
- 3.6mm fixed lens (2.8mm,6mm optional)
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- DC12V

### Technical Specification

<b>Model</b>	<b>DH-IPC-HDBW1000E-W</b>
	<b>Camera</b>
Image Sensor	1/4" 1Megapixel CMOS
Effective Pixels	1280 (H) x 720(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
Min. Illumination	0.01Lux/F1.8 (Color),0Lux/F1.8(IR on)
S/N Ratio	More than 50dB
Video Output	N/A
	<b>Camera Features</b>
Max. IR LEDs Length	30m
Day/Night	Auto(Electronic)/Color/B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas



Active System Integration

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

### Auxiliary Interface

Memory Slot	N/A
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A

### General

Power Supply	DC12V
Power Consumption	<4W
Working Environment	-30°C~+50°C, Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ110mm×81mm
Weight	0.39kg