



Active System Integration

## DH-IPC-HFW5200E-Z(VF)

2MP Full HD Network IR Bullet camera

www.asi.ind.in



### Features

- 1/2.8" 2Megapixel progressive scan Exmor CMOS
- H.264 & MJPEG dual-stream encoding
- Day/Night(ICR), AWB, AGC, BLC
- 3.6mm fixed lens (2.8mm,6mm optional)
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- DC12V

### Technical Specification

Model	DH-IPC-HFW5200E-VF	DH-IPC-HFW5200E-Z
<b>Camera</b>		
Image Sensor	1/2.8" 2Megapixel progressive scan Exmor CMOS	
Effective Pixels	1920(H)x1080(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/10000s	
Min. Illumination	0.01Lux/F1.4(Color), 0Lux/F1.4(IR on)	
S/N Ratio	More than 50dB	
Video Output	1 port	
<b>Camera Features</b>		
Max. IR LEDs Length	30m	
Day/Night	Auto(ICR) / Color / B/W	
Backlight Compensation	BLC / HLC / DWDR	
White Balance	Auto/Manual	
Gain Control	Auto/Manual	
Noise Reduction	3D	
Privacy Masking	Up to 4 areas	



Active System Integration

[www.asi.ind.in](http://www.asi.ind.in)

## Technical Specification

### Auxiliary Interface

Memory Slot	N/A
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A

### General

Power Supply	DC12V
Power Consumption	<4W
Working Environment	-30°C~+50°C, Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	273.3mm x 94.8mm x 94.8mm
Weight	1.25kg