



Active System Integration

DH-SD32203S-HN

2MP Full HD Network Mini PTZ Dome camera

www.asi.ind.in



Technical Specification

Model	DH-SD32203S-HN
	Camera
Image Sensor	1/2.8" Exmor CMOS
Effective Pixels	1944(H) x 1092(V), 2 Megapixels
Scanning System	Progressive
Electronic Shutter Speed	1/1 - 1/30,000s
Min. Illumination	Color: 0.05 lux@F1.6, B/W: 0.005 lux@F1.6
S/N Ratio	More than 50dB
Camera Features	
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto / Manual
Noise Reduction	2D / 3D
Privacy Masking	Up to 24 areas
Digital Zoom	16x

Features

- 3.0mm ~ 9.0mm(3x)optical zoom
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080p resolution
- Up to 255 presets, 5 auto scan, 8 tour, 5 pattern
- DWDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, AWB, AGC,BLC
- Max 240 °/s pan speed, 0° ~360° endless pan rotation
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- Built-in 2/1 alarm in/out
- Support intelligent 3D positioning with DH-SD protocol
- Micro SD memory, IP66, IK10, PoE



Active System Integration

www.asi.ind.in

Technical Specification

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF	ONVIF Profile S
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone

Auxiliary Interface

Memory Slot	Micro SD, Max 64GB
-------------	--------------------

General

Power Supply	DC12V, PoE(802.3af)
Power Consumption	10W
Working Environment	-20°C ~ 60°C / Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Dimensions	Φ160(mm) x 132(mm)
Weight	1.33kg