



BE-8008H

8Ch H.264 Standalone DVR System



- H.264 Stand-alone DVR
- 8 Video & 4 Audio Input
- Video Total Frame Rate: 200fps, PAL, 25fps per Channel, real-time
- High Image quality.
- Video Magnification through Mouse
- Pentaplex: Live / Record / Playback / Network / Mobile Phone
- User friendly Menu Settings, Front Panel, Mouse and Remote.
- Accommodates 1 SATA HDD (max.)
- Recording resolution up to 720x480 D1 resolution
- Search: Calendar and Log file.
- One Channel or Multi Channel video backup capability
- Support Host USB backup, Built-in File viewer on copy media
- High speed network transmission
- Remote Backup and Playback via IE Browser
- CMS (Central Management software) 100Ch display/screen and DVR connectivity
- Supports Static & Dynamic IP



Specifications:

Video Format		PAL
Video Input	8 Ch Input / BNC	
Audio Input	4 Ch Input / RCA	
Video Output	1CH Output / BNC	
Audio Output	1CH Output / RCA	
XGA Output	640x480、800x600、1024x768、1280x1024、1440x900	
Alarm Input	4CH Alarm In	
Alarm Output	Buzzer、1 x Relay Out (N.O、N.C)	
Display Mode	Full Screen, 4/8ch Split Screen, Auto Switch, Picture in Picture	
Display Resolution	720 x 576	
Recording Resolution	Highest	720 x 576
	High	720 x 288
	Normal	360 x 288
Recording Frame	Max. 200 FPS	
Compression Algorithm	H.264	
Operating System	Embedded Linux	
Pentaplex	Live / Record / Playback / Network / Mobile Phone	
Recording Mode	Manual, Schedule, Event	
Schedule Recording	Full Recording, Motion, Alarm, Manual Recording	
Status Indicator	Power, Recorder, Play	
Event Mode	Alarm Trigger, Motion Trigger, Video Loss Recording Duration: 10~60 sec.	
Playback Mode	Normal Speed: x1	
	Fast Forward: x2 / x4 / x8 / x16 multiple speed	
	Slow Forward: 1/2、1/4、1/8 multiple speed	
	Fast Rewind: x2 / x4 / x8 / x16	
	Frame by Frame Playback: Forward Search Function: Time / Event	
Network Protocol	TCP/IP / PPPoE / DHCP / SMTP / DDNS	
HDD Type	SATA 3.5"HDD x 1 (HDD not included)	
HDD Management	Automatic Format System	
PTZ Control	Communication Protocol (PELCO P, PELCO D)	
Backup Device	USB 2.0 Flash Memory Stick	
Firmware Update	Host USB	
Multi-Language	English / Chinese / Others	
Control Mode	Front Panel / Remote Control / USB Mouse / Internet	
Network Control	IE Browser	
Network Function	Live Display / Playback / PTZ Control / System Setup	
Mobile Phone	IE browser supported for mobile-phone surveillance	
Power Supply	DC 12V / 3A(AC100V~240V 50/60HZ)	
Unit Dimension	220mm (W)x 288mm (D) x 48 mm (H)	
Weight	Unit Weight 1.6kg (HDD and Power Adapter Not Included)	
Operating Temperature	0℃ ~ 46℃	