

BE - 8104H

H.264, 4Ch Video & 4Ch Audio, 3G Support



Features :

- H.264 Standalone DVR
- 4Ch Video & 4Ch Audio
- Real-time Display & Rec.
- Pentaplex
- Tamper-Proof Panel
- Up to 720x480 (D1) Record res.
- 3G Dongle Support
- 1HDD (3TB max)
- Hi-Speed network Transmission
- Free Apple & Android Mobile Apps



Optional

Specifications :

Type	BE-8104H
Video Format	PAL
Video Input	4 CH Input/BNC
Audio Input	4 CH Input/RCA
Video Output	1 CH Output/BNC
Audio Output	1 CH Output/RCA
XGA Output	800x600, 1024x768, 1280x1024, 1440x900
Alarm Input	N/A
Alarm Output	N/A
Display Mode	Full Screen ,4CHS Split Screen, Auto Switch, Picture in Picture
Display Resolution	720 x 576
Recording Resolution	Highest
	High
	Normal
Recording Frame	Max. 100 FPS
Compression Algorithm	H.264
Operating System	Embedded Linux
Pentaplex	Live/Record/Playback/Network/Mobile Phone
Recording Mode	Manual, Schedule, Event
Schedule Recording	Full Recording, Motion, Manual Recording
Status Indicator	Power, Network, HDD
Event Mode	Motion Trigger, Video Loss
	Recording Duration : 10~60 sec.
Play Mode	Normal Speed : x1
	Fast Forward : x2/x4/x8/x16/x32 Multiple Speed
	Slow Forward : 1/2 ~ 1/4 ~ 1/8 Multiple Speed
	Fast Rewind: x2/x4/x8/x16/x32
	Frame by Frame Playback: Forward
	Search Function: Time/Event
Network Protocol	TCP/IP/PPPoE/DHCP/SNMP/DDNS/3G
HDD Type	SATA 3.5" HDD x 1 (HDD Not Included)
HDD Management	Automatic Format System
PTZ Control	Communication Protocol (PELCO P, PELCO D)
Backup Device	USB 2.0 Flash Memory Stick
Firmware Update	Host USB
Multi-Language	English/Chinese/Others
Control Mode	Remote Control/USB Mouse/Internet
Network Control	IE Browser
Network Function	Live Display/Playback/PTZ Control/System Setup
Power Supply	DC 12V/3A (AC 100V~240V 50/60HZ)
Unit Dimension	220mm (W) x 215mm (D) x 50mm (H)
Weight	0.45kg (HDD and Power Adapter Not Included)
Operating Temp.	0°C ~ +46°C